



RJ-150™ EMERGENCY CHLORINE SCRUBBER

Evoqua Water Technologies offers a full range of emergency scrubbers for protection against accidental leaks of toxic gasses such as chlorine, ammonia and sulfur dioxide.

RJ-150™ Emergency Scrubber

The RJ-150 emergency chlorine scrubber is designed to contain and neutralize chlorine vapors released from a bank of 150 lb (70 kg) chlorine cylinders.

The RJ-150 scrubber uses a unique horizontal flow path, with a proprietary caustic distribution network, to absorb better than 99.999% of the chlorine gas entering the scrubber, in a very compact footprint and low profile.

The RJ-150 is the only emergency scrubber to have been tested by an independent, certified laboratory in a full 150-lb chlorine gas release. During this test a catastrophic accident was simulated with chlorine release rates of over 28 lb/min. The scrubber saw inlet concentrations in excess of 300,000 ppm, and outlet concentrations less than 1 ppm, safely below 5 ppm UFC limit.

How It Works

When a leak occurs, the pump and fan start automatically. The fan provides sufficient vacuum to contain the chlorine gas and deliver it to the scrubber. The pump circulates concentrated caustic solution over the scrubber packing to absorb virtually all of the chlorine gas.

Systems are typically designed for 2, 4 or 6 on-line cylinders. Systems are designed for 250 cfm air flow.

Packaged systems are available which provide chlorine cylinder storage, chlorination system and chlorine scrubber on a single skid.

Standard Features

- Patented System
- Proven in independent testing
- Compact, low profile suitable for indoor or out door installation
- Mounts on bulk caustic tanks to provide high Cl₂ capacity
- FRP Construction
- Evoqua Service and Support

RJ-150™ DESIGN INFORMATION

System	Number of Cylinders online	Airflow Rate	Caustic Volume	Dimensions LxWxH	Shipping Wt	Operating Wt	Fan Motor	Pump Motor
		cfm	gallons	ft	lbs	lbs	HP	HP
		<i>m³/h</i>	<i>liters</i>	<i>mm</i>	<i>kg</i>	<i>kg</i>	<i>kW</i>	<i>kW</i>
RJ-150-2	2	250	275	7.0 x 3.0 x 4.83	1,000	4,000	1.0	5
		425	1040	2133 x 914 x 1472	454	1814	0.75	3.7
RJ-150-4	4	250	550	7.0 x 3.0 x 6.58	1,500	7,500	1.0	5
		425	2082	2133 x 914 x 2006	680	3402	0.75	3.7
RJ-150-6	6	250	660	7.0 x 3.0 x 7.5	2,000	9,200	1.0	5
		425	2500	2133 x 914 x 2286	907	4173	0.75	3.7



Email odorcontrol@evoqua.com or visit www.evoqua.com/rj150 to connect with an expert.



181 Thorn Hill Road, Warrendale, PA 15086

+1 (866) 926-8420 (toll-free)

+1 (978) 614-7233 (toll)

www.evoqua.com

Certain features of this product are covered by U.S. Patent no. 5,518,696. RJ-150 is a trademark of Evoqua.

All information presented herein is believed reliable and in accordance with accepted engineering practices. Evoqua makes no warranties as to the completeness of this information. Users are responsible for evaluating individual product suitability for specific applications. Evoqua assumes no liability whatsoever for any special, indirect or consequential damages arising from the sale, resale or misuse of its products.

© 2014 Evoqua Water Technologies LLC

Subject to change without notice

OC-RJ150-DS-1114